




6200 Cochran Rd.
Solon, Ohio 44139
888-972-7848 - Toll Free
440-349-5432 - Fax
www.wraptite.com -
info@wraptite.com



Product Data Sheet

1.9 Mil Carton Sealing Tape



Product Description:

General performance, economical carton sealing tape with acrylic emulsion adhesive with performance in all temperatures. Resistant to weathering and yellowing.

Backing:	1.12 Mil
Adhesive:	Acrylic emulsion adhesive.
Color(s):	Clear.
Elongation (% At Break)	166% (ASTM D3759)
Tensile Strength	19 lbs. / in (ASTM D3759)
Adhesion to Steel	32.57 ozf / in (ASTM D3330)
Total Thickness:	1.9 Mil (ASTM D3652)
Temperature Range:	23°F to 104°F (Application) 0°F to 200°F (Operating)
Packaging	N/A
Country of Origin	N/A

Item ID Numbers

Here: 19CST2110C &
19CST3110C

Wrap-Tite, Inc.

6200 Cochran Rd.
Solon, Ohio 44139

Toll Free: 888-WRAP-TITE

Fax: 440-349-5432
www.wraptite.com -
info@wraptite.com

We believe the statements and information contained herein are accurate but are to be used only as general guidelines and are not warrants or guarantees because of the variety of possible uses. THERE IS NO WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE. THE BUYER MUST TEST THE SUITABILITY FOR EACH INTENDED APPLICATION BEFORE USING. WRAPTITE WILL NOT BE LIABLE FOR DAMAGES IN EXCESS OF THE PURCHASE PRICE OF ITS PRODUCTS OR FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES.