



6200 Cochran Rd.  
 Solon, Ohio 44139  
 888-972-7848 - Toll Free  
 440-349-5432 - Fax  
 www.wraptite.com -  
 info@wraptite.com



## Product Data Sheet

### 2.00 Mil Carton Sealing Tape -Machine Length



#### Product Description:

General performace, economical carton sealing tape with acrylic emulsion adhesive with performace in all temperatures. Resistant to weathering and yellowing.

**Item ID Numebrs**  
**Here:** 20CST21000C,  
 20CST21500C,  
 20CST31000C

**Wrap-Tite, Inc.**  
 6200 Cochran Rd.  
 Solon, Ohio 44139  
**Toll Free:** 888-WRAP-TITE  
**Fax:** 440-349-5432  
 www.wraptite.com -  
 info@wraptite.com

<b>Backing:</b>	1.10 Mil
<b>Adhesive:</b>	Acrylic emulsion adhesive
<b>Color:</b>	Clear.
<b>Elongation (% At Break)</b>	166% (ASTM D3759)
<b>Tensile Strength</b>	19 lbs./in
<b>Adhesion to Steel</b>	29.96 ozf/in (ASTM D3330)
<b>Total Thickness:</b>	2.00 Mil (ASTM D3652)
<b>Temperature Range:</b>	23°F to 104°F (Application) 0°F to 200°F (Operating)
<b>Packaging</b>	N/A
<b>Country of Origin</b>	N/A

We believe the statements and information contained herein are accurate but are to be used only as general guidelines and are not warrants or guarantees because of the variety of possible uses. THERE IS NO WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE. THE BUYER MUST TEST THE SUITABILITY FOR EACH INTENDED APPLICATION BEFORE USING. WRAPTITE WILL NOT BE LIABLE FOR DAMAGES IN EXCESS OF THE PURCHASE PRICE OF ITS PRODUCTS OR FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES.