



Product Data Sheet

2.0 mil HMA Tape



Effective 04/2019

Product Description:

HMA(Hot Melt Acrylic) Tape is the perfect replacement for the high-cost Synthetic Rubber Based Hot Melt Tape. Just like synthetic rubber, Hot Melt Acrylic has high initial tack and most importantly, does not leave any residue on the rollers of automatic taping heads. This tape is UV-resistant with excellent aging characteristics which works in a range of temperatures

Item ID Numbers:

20HMA2110C,20HMA3110C,20HMA21000C,20HMA31000C

Nominal Values:

Film thickness:	1.14 mil	
Adhesive:	Hot melt Acrylic	
Adhesive thickness:	0.83 mil	
Color:	Yellow transparent	
Total Thickness:	1.97 MIL	
Adhesion to Steel: (min.)	19.40 oz/in	(ASTM D3330)
Breaking Strength: (Max, Min 10%)	19.84 lb./in	(ASTM D3759)
Elongation: (Max, Min 10%)	180%	(ASTM D3759)
Shear strength (on paper)	2 hr. (min.)	(ASTM D3654)
Rolling ball tack (Max.)	551 Mils	PSTC-6
Service Temperature F°(Min / Max)	14 / 158 ° F	

We believe the statements and information contained herein are accurate but are to be used only as general guidelines and are not warrants or guarantees because of the variety of possible uses. THERE IS NO WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE. THE BUYER MUST TEST THE SUITABILITY FOR EACH INTENDED APPLICATION BEFORE USING. WRAPTITE WILL NOT BE LIABLE FOR DAMAGES IN EXCESS OF THE PURCHASE PRICE OF ITS PRODUCTS OR FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES.

Wrap Tite, Inc.
6200 Cochran Rd.
Solon, Ohio 44139
Toll Free: 888-WRAP TITE (972-7848)
Fax: 440-349-5432
www.wraptite.com - info@wraptite.com

