



Product Data Sheet

20HMT-RC Series Hotmelt Tape (for recycled boxes)



Effective 09/2018

Product Description:

Medium grade BOPP backed film carton sealing tape specially manufactured with Corru-Grip™ pressure-sensitive hot melt adhesive for optimal closure of recycled corrugate boxes, and in application environments down to 35°F. Excellent processing performance whether manually or automatically applied. Superior adhesion properties, holding force, tensile strength, and easy unwind ensure consistent, **reliable seals to a variety of corrugated and linerboard boxes, including recycled corrugate.**

Item ID Numbers:

20HMT2110C-RC,20HMT3110C-RC,20HMT21000C-RC,20HMT31000C-RC

Nominal Values:

Backing:	1.2 mils(0.030mm) (Cast film)	
Adhesive:	Synthetic Rubber /Resin	
Colors:	Clear	
Total Thickness:	2.05 mils(0.052mm)	(ASTM D3652)
Adhesion to Steel:	42 oz/in (46 N/100 mm)	(ASTM D3330)
Tensile Strength:	24 lb _f /in (420N/100mm)	(ASTM D3759)
Elongation (% at break)	130%	(ASTM D3759)
Temperature Range:	+35°F to +120°F (Application) -10°F to 140°F (Operating)	
Government Compliance:	Complies with the Federal Food, Drug and Cosmetic Act, CFR Title 21, Subpart B, Par. 175.105 (covers the use of pressure-sensitive adhesives and tapes for 'indirect contact' food packaging, such as box sealing). CID A-A-1684C.	

We believe the statements and information contained herein are accurate but are to be used only as general guidelines and are not warrants or guarantees because of the variety of possible uses. THERE IS NO WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE. THE BUYER MUST TEST THE SUITABILITY FOR EACH INTENDED APPLICATION BEFORE USING. WRAPTITE WILL NOT BE LIABLE FOR DAMAGES IN EXCESS OF THE PURCHASE PRICE OF ITS PRODUCTS OR FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES.

Wrap Tite, Inc.
6200 Cochran Rd.
Solon, Ohio 44139
Toll Free: 888-WRAP TITE (972-7848)
Fax: 440-349-5432
www.wraptite.com - info@wraptite.com

