



PVC Tape



Product Data Sheet

Effective 05/2018

Product Description:

Single sided carton sealing tape, suitable for use on standard and most recycled cartons; available in brown and transparent version.

- Good adhesion in several applications
- Performing even at low temp
- Suitable for use on most recycled cartons
- Good elongation
- No noise unwinding

Item ID Numbers:

21PVC1255T, 21PVC1255C, 21PVC1355C, 21PVC12110C, 21PVC12110T

Nominal Values:

Thickness:	2.1 mils (PSTC 133)
Adhesive:	Natural Rubber and Resins
Adhesive to steel:	13 oz./in width (PSTC 101 )
Color:	Transparent, Brown
Backing:	1.3 mil PVC Film
Tensile Strength:	28 lb./ in (PSTC 131)
Elongation (% at break)	60 % (PSCT 131)
Temp. Resistance (Max.)	140°F
Recommended Storage Condition	Store in original packaging in a cool, clean dry place away from direct sunlight. Temperature of 40 -80° F (4-26° C) and relative humidity of 40 to 50% relative humidity is recommended. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

We believe the statements and information contained herein are accurate but are to be used only as general guidelines and are not warrants or guarantees because of the variety of possible uses. THERE IS NO WARRANTY OF FITNESS FOR A PURPOSE. THE BUYER MUST TEST THE SUITABILITY FOR EACH INTENDED APPLICATION BEFORE USING. WRAPTITE WILL NOT BE LIABLE FOR DAMAGES MORE THAN THE PURCHASE PRICE OF ITS PRODUCTS OR FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES.

**Wrap Tite, Inc.**  
 6200 Cochran Rd.  
 Solon, Ohio 44139  
**Toll Free:** 888-WRAP TITE (972-7848)  
**Fax:** 440-349-5432  
[www.wraptite.com](http://www.wraptite.com) - [info@wraptite.com](mailto:info@wraptite.com)

