



Product Data Sheet

Aluminum Foil Tape



Effective 01/2017

Product Description:

3.0 mil dead soft aluminum foil with aggressive pressure-sensitive acrylic adhesive. Provides instant, water-resistant adhesion to clean, dry surfaces. Adheres well to itself (where overlapped) yet dispenses from the roll for easy application. Conforms to irregular/curved surfaces as it remains flexible and resists cracking and lifting. Also, UV resistant. Recommended minimum application temperature: 35°F.

Item ID Numbers:

AFTSW05.5, AFTSW05075, AFTSW0501, AFTSW0502, AFTSW0503



Nominal Values:

Backing:	3 mil dead soft aluminum foil
Adhesive:	Acrylic
Total Thickness:	4.7 mils (PSTC-133)
Adhesion to Steel:	55 oz/in (PSTC-101)
Tensile Strength:	29 lb./in (PSTC-131)
Elongation (% at break)	7.5%
Operating Temperature Range	-30 deg F - +325 deg F
Government Compliance	BAC D6-34501, Rev. H SAE-AMS-T-23397B. UL-723.

We believe the statements and information contained herein are accurate but are to be used only as general guidelines and are not warrants or guarantees because of the variety of possible uses. THERE IS NO WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE. THE BUYER MUST TEST THE SUITABILITY FOR EACH INTENDED APPLICATION BEFORE USING. WRAPTITE WILL NOT BE LIABLE FOR DAMAGES IN EXCESS OF THE PURCHASE PRICE OF ITS PRODUCTS OR FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES.

Wrap Tite, Inc.
6200 Cochran Rd.
Solon, Ohio 44139
Toll Free: 888-WRAP TITE (972-7848)
Fax: 440-349-5432
www.wraptite.com - info@wraptite.com

