



Product Data Sheet

Bag Sealing Tape



Effective 05/2021

Product Description:

General Performance, Bag sealing tape made from Natural Rubber adhesive with PVC backing.

- Good adhesion in several applications
- Performing even at low temp
- Good elongation
- No noise unwinding

Item ID Numbers:

BTI38W, R, Y, G, L

Nominal Values:

Thickness:	2.3 mils (PSTC 133)
Adhesive:	Natural Rubber and Resins
Adhesive to steel:	17 oz./in width (PSTC 101)
Color:	Red
Backing:	1.5 mil PVC Film
Tensile Strength:	28 lb./ in (PSTC 131)
Elongation (% at break)	70 % (PSCT 131)
Temp. Resistance (Max.)	140°F
Recommended Storage Condition	Store in original packaging in a cool, clean dry place away from direct sunlight. Temperature of 40 -80°F (4-26° C) and relative humidity of 40 to 50% relative humidity is recommended. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

We believe the statements and information contained herein are accurate but are to be used only as general guidelines and are not warrants or guarantees because of the variety of possible uses. THERE IS NO WARRANTY OF FITNESS FOR A PURPOSE. THE BUYER MUST TEST THE SUITABILITY FOR EACH INTENDED APPLICATION BEFORE USING. WRAPTITE WILL NOT BE LIABLE FOR DAMAGES MORE THAN THE PURCHASE PRICE OF ITS PRODUCTS OR FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES.

Wrap Tite, Inc.
6200 Cochran Rd.
Solon, Ohio 44139
Toll Free: 888-WRAP TITE (972-7848)
Fax: 440-349-5432
www.wraptite.com - info@wraptite.com

