



Product Data Sheet

Blue Painters Tape



Effective 01/2016

Product Description:

This product is a high-performance masking tape for general industrial, construction and do-it-yourself use. The acrylic adhesive system will not dry out and lose holding power and the product will cleanly remove from most surfaces for up to 21 days. The product works on drywall, glass, hardwood floors, wood trim, and a variety of other surfaces. The most typical use is paint and window masking. Application of the product and preparation and nature of the substrate are factors which will affect the product performance. The end user must determine its suitability for use.

Item ID Numbers:

BPT5618L , BPT5624L , BPT5638L , BPT5648L , BPT5672L

Nominal Values:

Adhesion to Steel :	19.0 to 22.0 oz/in (PSTC 1)
Tack level :	High
Tensile Strength :	20 lb./sq. in (PSTC 31)
Elongation (%) :	9 % (PSCT 31)
Thickness :	5.7 mils (nominal) (PSTC 33)

We believe the statements and information contained herein are accurate but are to be used only as general guidelines and are not warrants or guarantees because of the variety of possible uses. THERE IS NO WARRANTY OF FITNESS FOR A PURPOSE. THE BUYER MUST TEST THE SUITABILITY FOR EACH INTENDED APPLICATION BEFORE USING. WRAPTITE WILL NOT BE LIABLE FOR DAMAGES MORE THAN THE PURCHASE PRICE OF ITS PRODUCTS OR FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES.

Wrap Tite, Inc.
6200 Cochran Rd.
Solon, Ohio 44139
Toll Free: 888-WRAP TITE (972-7848)
Fax: 440-349-5432
www.wraptite.com - info@wraptite.com

