



Carpet Protection Film

Product Data Sheet

Effective 11/2017

Product Description:

This is a temporary masking product designed to protect synthetic carpets from tracked in dirt, spills, dust and damage during high traffic conditions. The polyethylene film is a special blend which is resistant to tears and punctures from sharp items such as tools or high heels. The acrylic adhesive system allows for clean removal. This product should not be used in high humidity conditions or in outdoor applications.

Item ID Numbers:

CPF2450C , CPF24200C

Nominal Values:

Thickness:	2.2 mils	(PSTC 33)
Tack level:	High	
Tensile Strength:	11 lb./sq. in	(PSTC 31)
Elongation (%) :	630	(PSTC 31)

(Tolerance +/- 10%); We believe the statements and information contained herein are accurate but are to be used only as general guidelines and are not warrants or guarantees because of the variety of possible uses. THERE IS NO WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE. THE BUYER MUST TEST THE SUITABILITY FOR EACH INTENDED APPLICATION BEFORE USING. WRAPTITE WILL NOT BE LIABLE FOR DAMAGES IN EXCESS OF THE PURCHASE PRICE OF ITS PRODUCTS OR FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES

Wrap Tite, Inc.
6200 Cochran Rd.
Solon, Ohio 44139
Toll Free: 888-WRAP TITE (972-7848)
Fax: 440-349-5432
www.wraptite.com – info@wraptite.com

