

Product Data Sheet

Filament Tape (General Purpose)



Effective 06/2020

Product Description:

An economical fiberglass reinforced polypropylene film combined with an aggressive 'solventless' pressure-sensitive adhesive provides excellent adhesion to corrugated cartons and outstanding holding power & it is <u>designed for majority of</u> <u>packaging, palletizing, and unitizing applications</u>

Item ID Numbers:

FTG3924, FTG3948

Nominal Values:

Backing:		1.0 mil (25 μ) BOPP Film
Adhesive:		Synthetic Rubber/Resin
Total thickness		4.0 (0.102mm)
Adhesion to Steel	PSTC-101	63 oz /in (17.2N/25mm)
Tensile Strength	PSTC -131	110 lbs./in (482N/25mm)
Elongation: (% at break) PSTC-131		3.5
Quick Stick (oz/in of width) To Kraft To Steel		8 (2.2N/25mm) 30 (8.2N/25mm
Shear to Kraft Paper (hrs.)		> 96
Color		Clear

We believe the statements and information contained herein are accurate but are to be used only as general guidelines and are not warrants or guarantees because of the variety of possible uses. THERE IS NO WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE. THE BUYER MUST TEST THE SUITABILITY FOR EACH INTENDED APPLICATION BEFORE USING. WRAPTITE WILL NOT BE LIABLE FOR DAMAGES IN EXCESS OF THE PURCHASE PRICE OF ITS PRODUCTS OR FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES.

> Wrap Tite, Inc. 6200 Cochran Rd. Solon, Ohio 44139 Toll Free: 888-WRAP TITE (972-7848) Fax : 440-349-5432 www.wraptite.com - info@wraptite.com

