



Product Data Sheet

**WAT Gum Tape
(Medium Duty)**



Effective 10/2018

Product Description:

Reinforced water activated tape features fiberglass reinforcement for added strength and durability. This is being used for closure of light to heavy boxes.



Item ID Numbers: GTI72KAR-WT

Nominal Values:

Top Sheet:

23.0#/3000 Sq. Ft Natural Virgin Kraft

Bottom Sheet:

23.0#/3000 Sq. Ft Natural Virgin Kraft

Laminating Adhesive:

Polyolefin Based (complies with FDA; CFR175.105)
15.5#/3000 Sq. Ft.

MD Reinforcement:(fiberglass)

G75 1/0 Denier1-1-1-1-1, on 1/2" spacing per72 mm. 2.76#/3000 Sq. Ft.

CD Reinforcement:(fiberglass)

G150 1/0 Denier on 1 1/4" Diamond Pattern Spacing 1.37#3000 Sq. Ft

Adhesive:

14.5#/3000 Sq. Ft (Modified Corn Starch Based)

Physical Properties:

Caliper:

5.9 to 6.9 mils

Weight:

80.6#/3000 Sq. Ft

Tensile Strength:

55-60 lbs./in MD

22-27 lbs./in CD

We believe the statements and information contained herein are accurate but are to be used only as general guidelines and are not warrants or guarantees because of the variety of possible uses. THERE IS NO WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE. THE BUYER MUST TEST THE SUITABILITY FOR EACH INTENDED APPLICATION BEFORE USING. WRAPTITE WILL NOT BE LIABLE FOR DAMAGES IN EXCESS OF THE PURCHASE PRICE OF ITS PRODUCTS OR FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES.

Wrap Tite, Inc.

6200 Cochran Rd.

Solon, Ohio 44139

Toll Free: 888-WRAP TITE (972-7848)

Fax: 440-349-5432

www.wraptite.com - info@wraptite.com

