

Re-Inforced Gum Tape (White)



Effective 06/2020

Product Data Sheet

Product Description:

It is a reinforced water activated tape designed for sealing corrugated cartons.

Item ID Numbers: GTI72WAR-WT

Composition:

Materials	Description	Value	
Kraft Paper (Top Sheet)	Bleached Virgin Kraft	25.0#/3000 Sq. Ft.	
Kraft Paper (Bottom Sheet)	Bleached Virgin Kraft	25.0#/3000 Sq. Ft.	
Laminate Adhesive	Polyolefin Based Complies with FDA; CFR 175.105	16.0#/3000 Sq. Ft.	
MD Reinforcement	Fiberglass	H110 1/0 Denier 1-1-1-1-1, on 33/64" Spacing. 2.14#/3000 Sq. Ft.	
CD Reinforcement	Fiberglass	G150 1/0 Denier on 1 ¼" Diamond Pattern Spacing. 1.37#/3000 Sq. Ft.	
Adhesive	Modified Corn Starch Based	15#/3000 Sq. Ft.	

Physical Properties:

Properties	Test Method	Typical Values
Basis Weight	TAPPI T410	84.5#/3000 Sq. Ft.
Caliper/Thickness	TAPPI T411	5.5 to 6.5 mils
Tensile Strength	ASTM D-828	49-55 lbs./in MD
		21-25 lbs./in CD

Packaging:

Sizes	Rolls/Carton	CS / Pallet
72mm x 450'	10	60

We believe the statements and information contained herein are accurate but are to be used only as general guidelines and are not warrants or guarantees because of the variety of possible uses. THERE IS NO WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE. THE BUYER MUST TEST THE SUITABILITY FOR EACH INTENDED APPLICATION BEFORE USING. WRAPTITE WILL NOT BE LIABLE FOR DAMAGES IN EXCESS OF THE PURCHASE PRICE OF ITS PRODUCTS OR FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES.

Wrap Tite, Inc. 6200 Cochran Rd. Solon, Ohio 44139 Toll Free: 888-WRAP TITE (972-7848) Fax : 440-349-5432 www.wraptite.com - info@wraptite.com

