



Product Data Sheet

Hard Surface Protection Film (Blue)



Effective 06/2020

Product Description:

This product is a temporary protective mask designed for use on smooth (polished metals #3 and #4 stainless steel, painted aluminum, and similar surfaces) and semi-smooth surfaces (most hardwood floors and ceramic tiles). This product is with an acrylic adhesive system that allows for clean removal with minimal adhesion buildup. The film contains a 60-day UVI additive that ensures clean removal of the tape after prolonged exposure to sunlight. For semi smooth surface it can be easily applied by hand or with an applicator to protect from tracked in dirt, paint spills, dust, construction debris and damage. The many variations in floor substrates and the finishing techniques for each make it imperative that the user determines its suitability for use.

Item ID & Description

HSPF2450L : (Hard Surface Protection film, / 24"x 50', 15 rls/cs)

HSPL24200L: (Hard Surface Protection film, / 24"x 200', 6 rls/cs)

Nominal Values	HSPF2450L	HSPF24200L
Adhesion to Steel PSTC -101 (oz/in)	2.0-4.5	2.0-4.5
Tack Level	Medium	Medium
Tensile Strength PSTC-131 lb./mm ²	11	11
Elongation (%) PSTC - 131	325	325
Thickness PSTC-133	2.5 mils	3.0 mils

We believe the statements and information contained herein are accurate but are to be used only as general guidelines and are not warrants or guarantees because of the variety of possible uses. THERE IS NO WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE. THE BUYER MUST TEST THE SUITABILITY FOR EACH INTENDED APPLICATION BEFORE USING. WRAPTITE WILL NOT BE LIABLE FOR DAMAGES IN EXCESS OF THE PURCHASE PRICE OF ITS PRODUCTS OR FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES

Wrap Tite, Inc.
6200 Cochran Rd.
Solon, Ohio 44139
Toll Free: 888-WRAP TITE (972-7848)
Fax : 440-349-5432
www.wraptite.com – info@wraptite.com

