



Product Data Sheet

Masking Tape



Effective 05/2018

Product Description:

General Purpose Masking Tape for general use and simple jobs in the building, construction and industrial sectors. Recommended to remove within 30 hours.

- Good addition even on uneven surfaces
- Well conformable to most shaped surfaces
- Hand Tearable
- Easy removal, if removed as soon as paint is dry, without leaving residue

Item ID Numbers:

MSTE4318W, MSTE4324W, MSTE4336W, MSTE4348W

Nominal Values:

Thickness:	4.3 mils (PSTC 133)
Adhesive:	Natural Rubber and cross-linked Resins
Adhesive to steel:	14 oz./in width (PSTC 101)
Color:	White
Backing:	Saturated Crepe Paper
Tensile Strength:	18 lb./ in (PSTC 131)
Elongation (% at break)	8 % (PSTC 131)
Service Temperature(Max.)	140°F (for 30 minutes)
Recommended Storage Condition	Store in original packaging in a cool, clean dry place away from direct sunlight. Temperature of 40 -80° F (4-26° C) and relative humidity of 40 to 50% relative humidity is recommended. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

We believe the statements and information contained herein are accurate but are to be used only as general guidelines and are not warrants or guarantees because of the variety of possible uses. THERE IS NO WARRANTY OF FITNESS FOR A PURPOSE. THE BUYER MUST TEST THE SUITABILITY FOR EACH INTENDED APPLICATION BEFORE USING. WRAPTITE WILL NOT BE LIABLE FOR DAMAGES MORE THAN THE PURCHASE PRICE OF ITS PRODUCTS OR FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES.

Wrap Tite, Inc.
6200 Cochran Rd.
Solon, Ohio 44139
Toll Free: 888-WRAP TITE (972-7848)
Fax: 440-349-5432
www.wraptite.com - info@wraptite.com

