



Product Data Sheet

Masking Tape



Effective 05/2018

Product Description:

This general-Purpose masking tape has been designed for use as a utility grade crepe paper masking tape for non-critical applications. An excellent room temperature product which primary use includes packaging, bundling, labeling and numerous other applications where a pressure sensitive tape is needed. Designed for indoor use only and should not be subjected to outdoor exposure or prolonged sunlight as it may become difficult to remove. It is solvent and thinner resistant. Not suitable for spray painting, oven baking applications and is not recommended for exacting industrial masking.

Item ID Numbers:

MST5512W, MST5518W, MST5524W, MST5536W, MST5548W, MST5572W

Nominal Values:

Thickness:	4.3 mils
Adhesive:	Natural Rubber and cross-linked Resins
Adhesive to steel:	20 oz./in width (ASTM D3330)
Color:	Ivory
Backing:	Saturated Semi-Crepe Paper
Tensile Strength:	22 lb./ in (ASTM D3759)
Elongation (% at break)	5 % (ASTM D3759)
Service Temperature(Max.)	122°F (for 30 minutes)
Recommended Storage Condition	Store in original packaging in a cool, clean dry place away from direct sunlight. Temperature of 40 -80° F (4-26° C) and relative humidity of 40 to 50% relative humidity is recommended. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

We believe the statements and information contained herein are accurate but are to be used only as general guidelines and are not warrants or guarantees because of the variety of possible uses. THERE IS NO WARRANTY OF FITNESS FOR A PURPOSE. THE BUYER MUST TEST THE SUITABILITY FOR EACH INTENDED APPLICATION BEFORE USING. WRAPTITE WILL NOT BE LIABLE FOR DAMAGES MORE THAN THE PURCHASE PRICE OF ITS PRODUCTS OR FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES.

Wrap Tite, Inc.
6200 Cochran Rd.
Solon, Ohio 44139
Toll Free: 888-WRAP TITE (972-7848)
Fax: 440-349-5432
www.wraptite.com - info@wraptite.com

