



Cast Pre-Stretch Max 80 Technical Data Sheet

- Pre-Stretch Cast Film
- Re-inforced edges makes it nick proof
- Lightweight & ergonomic
- Reduces fatigue during application
- Available in various colors (Tinted) in certain gauges – Black, Blue, Green, Red, Orange, Yellow, Purple, White (Custom Colors are available up on request)
- Product Categories – EWHF, EWNW, EWPW



Thickness	ASTM D-4649	Mic	6.4 mic	7.4 mic	8.5 mic	10 mic	12 mic
Tensile Ultimate MD	ASTM D-882	PSI	16000	15500	15000	14800	13500
Tensile Ultimate TD	ASTM D-882	PSI	3200	3500	3800	4000	4200
Tensile Yield MD	ASTM D-882	PSI	6650	6950	7250	7350	7450
Tensile Yield TD	ASTM D-882	PSI	1150	1250	1400	1475	1525
Elongation MD	ASTM D-882	%	80	80	180	180	180
Elongation TD	ASTM D-882	%	690	690	690	690	690
Elmendorf Tear MD	ASTM D-1922	g/mil	180	180	180	180	180
Elmendorf Tear TD	ASTM D-1922	g/mil	680	680	680	680	680
Cling	ASTM D-5458	g/in	150	150	150	150	150

- *All values are representative of typical film performance and are not to be construed as manufacturing and/or sales specifications.*

Email: info@wraptite.com, **B2B:** www.wraptite.com
Head Quarters: 6200 Cochran Road, Solon, Ohio 44139
Phone: 440-349-5400

Mfg Website: www.wraptite.com/manufacturing/
Manufacturing: 6075 Cochran Road, Solon, Ohio 44139
Fax: 440-349-5432