



"Your Source For Packaging, Shipping & Safety Supplies"  
"Ship right with Wrap-Tite"



## Pre- Stretch NocoWrap Technical Data Sheet

- No core to throw away
- Superior Load Holding Strength
- 100% recyclable & eco-friendly
- Various handle options available
- Available in various colors (Dark & Tinted) – Black, Blue, Green, Red, Orange, Yellow, Purple, White (Custom Colors are available up on request)
- Product Categories – GW, GWNW

|                     |             |       |          |
|---------------------|-------------|-------|----------|
| Thickness           | ASTM D-4649 | Mic   | 8.5 mic. |
| Tensile Ultimate MD | ASTM D-882  | PSI   | 15000    |
| Tensile Ultimate TD | ASTM D-882  | PSI   | 3800     |
| Tensile Yield MD    | ASTM D-882  | PSI   | 7250     |
| Tensile Yield TD    | ASTM D-882  | PSI   | 1400     |
| Elongation MD       | ASTM D-882  | %     | 180      |
| Elongation TD       | ASTM D-882  | %     | 690      |
| Elmendorf Tear MD   | ASTM D-1922 | g/mil | 180      |
| Elmendorf Tear TD   | ASTM D-1922 | g/mil | 680      |
| Cling               | ASTM D-5458 | g/in  | 150      |



- *All values are representative of typical film performance and are not to be construed as manufacturing and/or sales specifications.*

**Email:** [info@wraptite.com](mailto:info@wraptite.com), **B2B:** [www.wraptite.com](http://www.wraptite.com)

**Head Quarters:** 6200 Cochran Road, Solon, Ohio 44139

**Phone:** 440-349-5400

**Mfg Website:** [www.wraptite.com/manufacturing/](http://www.wraptite.com/manufacturing/)

**Manufacturing:** 6075 Cochran Road, Solon, Ohio 44139

**Fax:** 440-349-5432