



## Product Data Sheet

### Tamper Evident Tape



Effective 08/2019

#### Product Description:

This industrial grade packaging tape is primarily used for sealing, splicing, bundling and other medium to heavy packaging applications. It's ideal for stopping pilferage.

**Item ID: 204810-ISB-H, 207210-ISB-H**

#### Print Image:



#### Nominal Values:

Backing type & thickness	BOPP & 1.1 mil	
Adhesive:	Synthetic Rubber	
Total Thickness:	1.83 mil	(ASTM D3652)
Adhesion to Steel:	32 oz/in	(ASTM D3330)
Tensile Strength:	27 lb./in	(ASTM D3759)
Elongation (% at break)	85%	(ASTM D3759)
Temperature Range:	+45°F to +120°F (Application) -10°F to +140°F (Operating)	

(Tolerance +/- 10%); We believe the statements and information contained herein are accurate but are to be used only as general guidelines and are not warrants or guarantees because of the variety of possible uses. THERE IS NO WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE. THE BUYER MUST TEST THE SUITABILITY FOR EACH INTENDED APPLICATION BEFORE USING. WRAPTITE WILL NOT BE LIABLE FOR DAMAGES IN EXCESS OF THE PURCHASE PRICE OF ITS PRODUCTS OR FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES.

**Wrap Tite, Inc.**  
6200 Cochran Rd.  
Solon, Ohio 44139  
**Toll Free:** 888-WRAP TITE (972-7848)  
**Fax:** 440-349-5432  
[www.wraptite.com](http://www.wraptite.com) - [info@wraptite.com](mailto:info@wraptite.com)

